

Magna-Blends™
All Natural Mineral Based Powder Mixes

Geo-Stucco 150™
Ceramic Stucco - Fine

DESCRIPTION:

A waterproof, moldproof, fireproof, non-toxic, non shrinking, ultra thin "breathing" ceramic exterior rock hard stucco "egg-shell" finish coat.

It is recommended to use with other quality ceramic *Magna-Blends* products.

COVERAGE AND SET-TIME:

As little as 1/16" total one coat system (.5lbs/sf) (min. 10 lbs per 4x8 sheet.-avg. 15 lbs 4x8 sheet) set time is 15-30 minutes at 75 deg & 60% humidity.

PREPARATION:

The surface must be clean and free of dust & debris—very light misting of the host surface recommended (dab off any excess beads of water)(dry to touch after dabbing)

MIXING:

Only mix in small batches that can be used up in ~15 minutes or less—must be mechanically mixed for 3-4 minutes –start with ~8% (by weight) water and add additional as need with spray bottle or drips to desired consistency (~thick milk shake)—when working in outdoor temps above 75 degrees use cold (ice) water to extend working time.

APPLICATION:

Apply with trowel or (recommended) with standard sheet rock texturing hopper sprayer—apply in smooth even strokes sprayed as a light splater or troweled ultra thin (1/8" or less) over smooth surface—be sure to have a designated "batching" person who is timed to refilling mud as soon as possible when first batch used up—never have the next batch waiting more than a few minutes before refilling.

CLEAN-UP:

Clean up all tools & equipment & buckets immediately with water—this product is very fast curing even under water—waste is non-toxic—. Disposable anywhere except plumbing.

SAFETY AND HEALTH WARNINGS: LUNG INJURY AND CANCER HAZARD.

Product contains free crystalline silica—prolonged inhalation can cause delayed lung injury including silicosis—avoid creating dust when handling—use only with adequate ventilation to limit exposure—follow all osha or other relevant safety & health standars pertaining to quartz crystalline silica (cas# 14808-60-7)